



agromeks

AGRICULTURAL MACHINERY



agromeks.com/en

We Are Building
The Green Future



agromeks
AGRICULTURAL MACHINERY

agromeks.com

Green Ecology,
Investment in
The Future







We Are Building
The Green Future





We produce for our farmers
who sow their sweat into

the soil





LEOPAR 200 Stone Crusher

NEW PRODUCT




LEOPAR 200




- Italian-designed transmission-



- Six-belt drive system-



-Carbide Diamond Crusher Rotor-



Introducing our new product, the Leopard-200, offering greater soil cultivation width and depth, allowing for soil cultivation up to 200cm wide and 40cm deep. Agromeks Leopard Stone Crushers not only purify agricultural lands from the negative effects of stones but also enrich the soil with minerals, creating a fertile agricultural environment. Our models with various working widths facilitate the grinding of stones and preparation of the soil on your land. These machines can be used in a wide range of applications including fields, orchards, greenhouses, vineyards, beaches, and non-agricultural industrial areas. Diamond Boron Carbide (Carbide) cutting teeth ensure long-lasting performance, while the steel chassis and body maximize durability, guaranteeing flawless operation even in the toughest working conditions. We have maximized durability by using specially manufactured Italian-designed transmissions in our machines. Furthermore, we have enhanced production quality by utilizing advanced technology equipment in our balancing and rotor preparation facilities.

| MODEL | 200 |
|-----------------------------------|-----------------|
| Working Width | 200cm |
| Required Tractor Power | Min.: 105hp |
| Required Tractor Feature | Super Slow Gear |
| Working Depth | Max: 20cm |
| Working Speed | 0,3-2 km/hr |
| Crusher Teeth Material | Bar Carbide |
| Machine Interior Coating Material | Hardox |
| PTO rpm | 540rpm |
| Crusher Teeth Architecture Desing | Helix |
| Fron Cover | Hydraulic |
| Oil Pump Supply Type | Tractor |
| Weight | 1820kg |
| Width | 205cm |
| Lenght | 115cm |
| Height | 135cm |
| Teeth Number | 34 pcs |



LEOPAR 150-170 Stone Crushers




LEOPAR 150-170



-Italian-designed transmission-



-Six-belt drive system-



-Carbide Diamond Crusher Rotor-



Agromeks Leopard Stone Crusher purify agricultural lands from the negative effects of stones, creating a productive farming environment while also enriching the soil with minerals. Our models with various working widths allow for the grinding of stones and preparation of the soil on your land. These machines can be utilized in a wide range of applications including fields, orchards, greenhouses, vineyards, beaches, and non-agricultural industrial areas. Diamond Boron Carbide (Carbide) cutting teeth ensure long-lasting performance, providing superior durability. The steel chassis and body maximize durability, guaranteeing flawless operation even in the most challenging working conditions. We have optimized durability by incorporating specially manufactured Italian transmissions into our machines. Additionally, we have enhanced production quality by utilizing advanced technology equipment in our balancing and rotor preparation facilities.

| MODEL | 150 | 170 |
|-----------------------------------|-----------------|-----------------|
| Working Width | 150cm | 170cm |
| Required Tractor Power | Min.: 80hp | Min.: 95hp |
| Required Tractor Feature | Super Slow Gear | Super Slow Gear |
| Working Depth | Max: 20cm | Max: 20cm |
| Working Speed | 0,3-2 km/hr | 0,3-2 km/hr |
| Crusher Teeth Material | Bor Carbide | Bor Carbide |
| Machine Interior Coating Material | Hardox | Hardox |
| PTO rpm | 540rpm | 540rpm |
| Crusher Teeth Architecture Desing | Helix | Helix |
| Fron Cover | Hydraulic | Hydraulic |
| Oil Pump Supply Type | Tractor | Tractor |
| Weight | 1465kg | 1665kg |
| Width | 178cm | 198cm |
| Lenght | 115cm | 115cm |
| Height | 130cm | 130cm |
| Teeth Number | 34 pcs | 34 pcs |

JAGUAR 185-210

Stone Pickers


NEW PRODUCTS



JAGUAR 185-210



- Springless articulated drum bearing system-



- Spring Screening System-



-Automatic chain tensioning system-



"Our new product stands out with the Springless Articulated Drum Bearing feature, which reduces the risks encountered by stone picking machines. Traditional machines can be damaged when dealing with large stones, but our new design minimizes this risk. The articulated drum bearing absorbs the load of the stones on the system and carries them without damaging the machine. This greatly reduces damage, lowers maintenance and operating costs. Additionally, our new product can effectively collect large stones, providing more capacity to agricultural operations. This enhances agricultural productivity while increasing machine durability and providing farmers with a competitive advantage. The Spring Mesh System prevents potential stone jams and also supports more effective screening of mud and soil by vibrating. The automatic chain tensioner effectively eliminates tension issues that may arise from changes in load on the chain. NEW - Springless and Articulated Drum Bearing System not only protects the machine against stone jams but also supports the smooth collection of larger diameter and heavier stones while increasing operating speed by 30%."

| Model | 185 | 210 |
|--|--------------|--------------|
| Working Width | 185 CM | 210 cm |
| Storage Capacity | Max. 6500 kg | Max. 9000 kg |
| Required Min. Tractor Power | 60-80 HP | 80 - 90 HP |
| Collectible Stone Diameter (min. , max.) | 3-55 cm | 3-55 cm |
| Working Depth (max.) | 35 cm | 35 cm |
| Weight | 3720 kg | 4053 kg |
| Length | 520 cm | 520 cm |
| Path Width | 255 cm | 280 cm |
| Height | 260 cm | 260 cm |
| Storage Height | 260 cm | 260 cm |

JAGUAR 140-175-200

Stone Pickers



JAGUAR 140-175-200




-Automatic chain tensioning system-



- Spring-loaded drum bearing system-



- Spring elimination system-



Agromeks - Jaguar - Stone Pickers play a critical role in the cultivation of rocky terrain in the agricultural sector. These machines collect stones from the surface up to a depth of 30 cm and simultaneously work the soil. They can also be used to clean shores and beaches. With capacities ranging from 3 cm to 65 cm in diameter, they are capable of collecting stones of various sizes. Our machines are manufactured with durable special steel materials and feature a specially designed clutch and transmission system for longevity. The blade and spring system can be easily replaced, while the storage system offers easy emptying capabilities. We offer models in different sizes, serving as a reliable partner to increase agricultural productivity.

| Model | 140 | 175 | 200 |
|--|--------------|--------------|--------------|
| Working Width | 140 cm | 175 cm | 200 cm |
| Storage Capacity | Max. 4500 kg | Max. 6000 kg | Max. 8500 kg |
| Minimum Tractor Power | 50 - 65 HP | 60 - 80 HP | 80 - 90 HP |
| Collectible Stone Size (min. ,max. diameter) | 3-35cm | 3-35cm | 3-35cm |
| Working Depth (max.) | 35 cm | 35 cm | 35 cm |
| Weight | 2800 kg | 3525 kg | 3850 kg |
| Lenght | 520 cm | 520 cm | 520 cm |
| Path Width | 225 cm | 255 cm | 280 cm |
| Height | 250 cm | 250 cm | 250 cm |
| Storage Height | 260 cm | 260 cm | 260 cm |




PARS Mulcher & Collector




PARS



-A rotor with a working width of 200cm. It features 42 conveying blades and 24 shredder blades-



-Conveying Rotor Chain Power Transmission, while the shredder rotor features a triple belt power transmission for safety purposes-



-Hydraulic Lift Storage System
A hydraulic lift storage system with a 1 m3 storage volume and a 180cm discharge height-



Agromeks - Pars - Branch Mulcher and Collector Machine offers a significant solution in orchard maintenance. With this innovative product, the effective collection and processing of diseased and unnecessary branches in orchards become possible. Additionally, the materials obtained during this process can be used in fertilizer and bioenergy production. The machine, with a working width of 200 cm, enables easy collection of pruned branches in orchards, greenhouses, and other agricultural areas. The collected branches are then processed, compacted, and made easier to transport. Agromeks - Pars - Branch Collection and Chopping Machine promotes the recycling of collected materials, providing environmental benefits and enabling economic gain. These materials become a valuable resource for pellet factories and bioenergy production facilities. Furthermore, in a period where labor costs are increasing, this machine significantly reduces labor costs, providing substantial savings to businesses. It is an ideal solution to increase efficiency in the agricultural sector and support universal sustainability.


| | |
|------------------------|--------------|
| Working Width | 200cm |
| Width | 215cm |
| Length | 300cm |
| Height | 177cm |
| Working Height | 265cm |
| Weight | 1450kg |
| Storage Capacity | 1m3 |
| PTO | 540rpm |
| Drum rpm | 1800-2000rpm |
| Speed | 5-10km/hr |
| Hydraulic Power Supply | Tractor |
| Required Tractor Power | Min. 55hp |
| Shredder Blade Type | Hammer |
| Shredder Blade Number | 24 |
| Crusher Drum Width | 170cm |
| Tyres | 16,5/6,5-80 |
| Warranty | 2 Years |




PANTER 10 Solid Manure Spreader Trailer



PANTER 10



-Double-Row Chain Conveyor System-



-Twin-tray and Threshing Distributor System-



-Powerful Transmission, Powerful Machine-



PANTER-10 stands out as a larger capacity agricultural machine. It is 725 cm long, 210 cm wide, and 240 cm high. This model weighs 3900 kg and utilizes a tandem axle system. It is equipped with a hydraulic conveyor system and has a capacity of 10 m³, which translates to a 12-ton fertilizer carrying capacity. It features a spiral motion operated by a tail shaft - PTO and 12 mm heat-treated chains. The tire size is 400/60-15.5. The minimum required power is 75 horsepower, with a tail shaft speed of 540 revolutions per minute. Fertilizer spreading width can be adjusted between 5-15 m. It comes with a 2-year warranty.

The Double-Row Chain Conveyor System transports the fertilizer uniformly. Its 12mm heat-treated chains are resistant to objects such as stones. The Twin-Tray, Threshing Distributors allow for fertilizer spreading up to 15 meters. Our specially designed transmissions are manufactured to withstand sudden load changes.


| | |
|-------------------------|--------------------------------|
| Capacity m3 | 10 m3 |
| Capacity Ton | 12 ton |
| Manurid Spread Area | 5-15 m |
| Minimum Tractor Power | 75 HP |
| PTO | 540 |
| Axxle Type | Double Axxle / Tandem Scissors |
| Lenght | 725cm |
| Width | 210cm |
| Height | 240cm |
| Weight | 3900kg |
| Conveyor | Hydraulic |
| Spiral Movement | PTO |
| Spiral Gearbox Number | 2 |
| Conveyor Gearbox Number | 1 |
| Protect System | Shoe Shaft |
| Spiral Number | 2 |
| Conveyor Type | 12 mm HEated Chain |
| Tires | 400/60-15,5 |
| Warranty | 2 Years |




PANTER 5 Solid Manure Spreader Trailer



PANTER 5




-Double-Row Chain Conveyor System-



-Twin-tray and Threshing Distributor System-



-Powerful Transmission, Powerful Machine-



PANTER-5 stands out as a larger capacity agricultural machine. It is 725 cm long, 210 cm wide, and 240 cm high. This model weighs 3900 kg and utilizes a tandem axle system. It is equipped with a hydraulic conveyor system and has a capacity of 10 m³, which translates to a 12-ton fertilizer carrying capacity. It features a spiral motion operated by a tail shaft - PTO and 12 mm heat-treated chains. The tire size is 400/60-15.5. The minimum required power is 75 horsepower, with a tail shaft speed of 540 revolutions per minute. Fertilizer spreading width can be adjusted between 5-15 m. It comes with a 2-year warranty. The Double-Row Chain Conveyor System transports the fertilizer uniformly. Its 12mm heat-treated chains are resistant to objects such as stones. The Twin-Tray, Threshing Distributors allow for fertilizer spreading up to 15 meters. Our specially designed transmissions are manufactured to withstand sudden

| | |
|-------------------------|--------------------|
| Capacity m3 | 6 m3 |
| Capacity Ton | 7 ton |
| Manurid Spread Area | 5-15 m |
| Minimum Tractor Power | 55 HP |
| PTO | 540 |
| Axxle Type | Single Axxle |
| Lenght | 606cm |
| Width | 210cm |
| Height | 230cm |
| Weight | 2940kg |
| Conveyor | Hydraulic |
| Spiral Movement | PTO |
| Spiral Gearbox Number | 2 |
| Conveyor Gearbox Number | 1 |
| Protect System | Shoe Shaft |
| Spiral Number | 2 |
| Conveyor Type | 12 mm Heated Chain |
| Tires | 400/60-15,5 |
| Warranty | 2 Years |




G-PANTER 4-6


Garden Type Solid Manure Fertilizer



G-PANTER 4-6



-Distance-adjustable covers



-Manure conveyor system



-Double tray spread system



Agromeks Panther Garden/Greenhouse Type Solid Fertilizer Distribution Trailers are effective agricultural equipment that enables the homogeneous distribution of solid animal fertilizers onto agricultural land, orchards, and vineyards. Our 4m³, 5m³, and 6m³ capacity models offer a wide variety with loading capacities of 5 tons, 6 tons, and 7 tons.

The single axle tandem scissor system, distinguished by its special design, offers excellent fuel efficiency and ease of use even with low horsepower tractors.

With adjustable spreading capacity from 1 to 8 meters, it provides quick and effective fertilizer distribution on large plots of land.

Furthermore, our product comes with an additional assurance of a 2-year service guarantee.

| | PANTER-4 | PANTER-6 |
|---------------------------------|--|------------------------------------|
| TYPE | Garden Model | Garden Model |
| LENGTH | 520 cm | 520 cm |
| WIDTH | 250 kg | 250 kg |
| HEIGHT | 157 cm | 157 cm |
| TYRES | 10.0/75 15.3 | 10.0/75 15.3 |
| WORKING WIDTH | 8 Mt Left or right adjustable (total 12mt) | 8 Mt Left or right (total 12mt) |
| CAPACITY | 4 [M ³] | 4 [M ³] |
| PTO | 540 RPM | 540 RPM |
| WORKING SPEED | 4-5 Km/H | 4-5 Km/H |
| CONVEYOR TYPE | 12mm Heated Chain | 12mm Heated Chain |
| SPREADER TYPE AND NUMBER | Disc Model - 2 PCS | Disc Model - 2 PCS |





SAVANA 3200

Shredder



SAVANA 3200



-In-Chasis Shredder-



-High Quality Blades-



-Strong PTO Gearbox-



Flail shredder; also known as Flail Mower or Chopper; is used to shred plant wastes after harvest. All the plant wastes and residues got broken in very little pieces. With the process, residues can dissolve in the soil easily. The process enhances soil microorganisms, so; soil quality. It can be also used as weed mower if needed. Plant wastes will be mixed with soil, therefore soil recovers its organic material. It also shreds the wet plant wastes and stems. It can be used for living plant stem and branch mowing too. Wider working width saves time and fuel in large fields.

| | |
|----------------------------------|--------------------|
| Model | SAVANA 3200 |
| Working Width | 320cm |
| Required Tractor HP(min.) | 70hp |
| Blade Quantity | 144 |
| Belt Quantity | 6 |
| Total Width | 345cm |
| Weight | 903 |
| PTO | 750 |

We Are Building The Green Future



www.agromeks.com/en
+90 850 242 44 45
+90 542 672 11 42
sales@agromeks.com

Adress:
Reis Mahallesi. Akşehir Organize Sanayi Bölgesi. 5.Sokak. No:22
Akşehir/Konya/TURKEY